K-200D



Wide-Format Durable Inkjet Label Printer



The **Kiaro® K-200D** is a digital label printer for large, durable labeling and prints wide labels that can withstand dirt, moisture or water submersion, abrasion and exposure to UV rays or sunlight- all while maintaining clarity and colorfastness at 1200 dpi.

Thanks to its cutting-edge pigment ink formulation and QuickLabel's qualified label stocks, labels printed by the **Kiaro® K-200D** comply with GHS hazard warning labeling regulations and possess BS5609 certification, one of the most stringent physical label standards in the world.

- Fast print speed up to 6 inches per second (30 ft per minute)
- Exceptional print resolution up to 1200 dpi
- Print width 4.3" to 8.4"
- Produce BS5609 and GHS Standard certified labels
- Perfect for larger products such as pallets, gallon/liter jugs and barrels

Technical Specifications

Operation:

•	
Ink Type:	Pigment ink, (4) individual CMYK cartridges
Print Resolution:	1200 x 1200 dpi
Print Speed:	2 ips (50 mm/sec) – 6 ips (150 mm/sec) User selectable and automatic
Print Area:	Width: 4.3" (108 mm) – 8.4" (212 mm) Length: 0.9" (22 mm) – 17.9" (454 mm)
Media Sensors:	Reflective
Connectivity:	USB 2.0, Gigabit Ethernet, and RJ-45 connection
Software:	Microsoft® Windows 10, 8, 7; Windows Server® 2012, 2008, 64/32-bit Drivers, CQL Pro advanced label creation and print management software (one free license included),or NiceLabel® software (optional)

Environmental & Physical:

Printer Operating:	59° F to 86° F (15° C to 30° C), 10% to 90% Relative Humidity (non-condensing)
Power Requirements:	115 – 230V, 60 – 50Hz, 3A/1.5A
Dimensions:	39.4" L x 21.9" W x 20.4" H (1001 mm x 556 mm x 518 mm)
Weight:	149 lbs. (68 kg) without supplies 154 lbs. (70 kg) with supplies
Optional Accessories:	Kiaro! 200D label rewinder

Supplies:

Ink Cartridges:	Kiaro!®D K-200D CMYK pigment cartridges, 240 mL each
Maintenance Cartridge:	450 mL full replacement; 360 mL (80%) near full warning
Ink Type:	Pigment-based, developed to withstand abrasion, resist moisture and has increased UV resistance

Labels and Tags:

Width:	4.9" (125 mm) – 9" (230 mm)
Length:	1.1" (29 mm) – 18.1" (460 mm)
Thickness:	5.7 mil (0.145 mm) – 10 mil (0.255 mm)
Roll Size:	Up to 12" (305 mm) outside diameter
Types:	Matte Paper and Synthetic pressure- sensitive; Paper Tag Stock

Warranty:

One-Year Manufacturer's Parts & Labor Warranty on printer (excludes wear parts and supplies)









Toll-free: 877-757-7978 | Tel: 401-828-4000 | info@quicklabel.com | www.quicklabel.com