

KIARO!® QL-120

# Professional Tabletop Digital Label Printer



## User-Friendly

### Field-Proven Design

- Quick setup
- Excellent web tracking to ensure perfect registration
- Easy access to media loading
- Built-in automatic cutter
- Roll-to-roll, roll-to-cut or z-fold capable

### Network-friendly

- Simple network configuration and administration
- Shared printing support across multiple locations and workstations
- Remote access to printer status

### Software

- CQL Pro advanced label design & print management software
- Color control available on a label field basis
- Easy-to-use software utility to monitor printer status

## Flexible and Productive

### Wide Range of Capabilities

- Print as narrow as 0.5" (12.7 mm)
- Precise and consistent full-bleed image placement onto die-cut labels
- Exclusive image processing and color matching accuracy to ICC color profiles
- Handles custom-shaped labels
- Windows driver compatible with all graphic design software
- Advanced external control and integration with label applicators

### Highly Productive

- Print up to 12 ips (305 mm/sec)
- Readability as small as 4pt. font size
- Print and rewind for automatic label application
- Less production stops with high roll capacity

## Cost-Effective

### Just-in-Time Label Production

- Eliminate label waste and reduce preprinted label inventory
- Print multiple label designs or variable information on-the-fly
- Maintain compliance with label revision or regulatory changes
- Avoid label vendor delivery or production delays
- Flexibility to handle short, medium or long runs

### Low Total Cost of Ownership

- Low energy consumption
- Automatic maintenance for optimal print quality
- Simple, user-changeable printhead
- Optimized ink usage
- Robust design for long lasting life

# Technical Specifications

## Operation:

<b>Ink Type:</b>	Dye ink, (4) individual CMYK cartridges
<b>Print Resolution:</b>	1200 x 1200 dpi
<b>Print Speed:</b>	12 ips (305 mm/sec) at 1200 x 600 dpi 8 ips (203 mm/sec) at 1200 x 1200 dpi/ 600 x 600 dpi
<b>Print Area*:</b>	Width: 0.5" (12.7 mm) - 4.2" max (106 mm) Length: 0.24" (6 mm) - 30" (762 mm)
<b>Media Sensors:</b>	Gap, Reflective (black mark), Continuous
<b>Cutter</b>	Automatic, guillotine-type, cut at end of batch or between labels, 1.0" (25.4 mm) minimum cut length Rated for 1.5 M cuts on 1.8 mil, 65 gsm glassine paper
<b>Connectivity:</b>	High-speed USB 2.0; gigabit ethernet RS-232 external control interface and protocol
<b>Software:</b>	Microsoft Windows® 10, 8.1, 8, 7; Windows Server® 2012, 2008, 64/32-bit drivers, CQL Pro advanced label creation and print management software (one free license included), Nicelabel® 2017 enterprise or desktop software (optional)

## Environmental & Physical:

<b>Printer Operating:</b>	59° F to 86° F (15° C to 30° C), 10% to 90% Relative Humidity (non-condensing)
<b>Power Requirements:</b>	100 - 240 VAC 50/60Hz, 1.5A/0.5A
<b>Power Consumption:</b>	Operating: 233W printer, 268W printer with cut operation Idle, Powered On: 22W (max) Standby/Sleep Mode: 8.5W Powered Off: 0.4W (Erp/Lot6)
<b>Dimensions:</b>	15.2" L x 22.4" W x 15.5" H (386 mm x 564 mm x 394 mm)
<b>Weight:</b>	52.9 lbs. (24 kg) without supplies 56.1 lbs. (26 kg) with supplies 68.2 lbs. (31 kg) shipping
<b>Optional Accessories:</b>	RW-5.1 Automatic Label Roll Rewinder, 11.8" (300 mm) OD Roll UW-5.1 Automatic Label Roll Unwinder, 11.8" (300 mm) OD Roll External Control Interface

## Supplies:

<b>Ink Cartridges:</b>	QuickLabel QL-120 CMYK dye cartridges, 240 mL (230 mL usable)
<b>Maintenance Cartridge:</b>	450 mL full replacement; 360 mL (80%) near full warning

## Labels and Tags:

<b>Construction**:</b>	Width: 1.0" (25.4 mm) - 4.53" (115 mm) Length: 0.24" (6 mm) - 30" (762 mm)
<b>Thickness:</b>	5.7 mil (0.145 mm) – 10 mil (0.255 mm)
<b>Roll Size:</b>	7.9" OD (201 mm), 3" ID (76 mm) core 11.8" OD (300 mm) with optional UW-5.1 External Unwind
<b>Types:</b>	Gloss Paper, Matte Paper and Synthetic pressure-sensitive; Paper Tag Stock

## Warranty:

One-Year Manufacturer's Parts & Labor Warranty on printer (excludes printhead and purge unit)



\* Consult with our media sales specialist for label widths narrower than 0.75" (19mm)

\*\* Construction = print width + edge trim